

Akış Kontrol Sistemleri



Genel Maksat - Ø9 Armatür

Normalde Kapalı 2/2

Sipariş Kodu	Ölçü	Orif. (mm)	Basınç (Bar)		Sıcaklık	Conta/Diyaf.	
			P Min	P Max			
1301-KDNA016-015	1/8"	1,5	0	16	-10 +80 °C	NBR	
1301-KDNA016-018	1/8"	1,8	0	16	-10 +80 °C	NBR	
1301-KDNA016-020	1/8"	2	0	16	-10 +80 °C	NBR	



Genel Maksat - Ø9 Armatür

Normalde Kapalı 2/2

Sipariş Kodu	Ölçü	Orif. (mm)	Basınç (Bar)		Sıcaklık	Conta/Diyaf.	
			P Min	P Max			
1301-KDNB016-015	1/4"	1,5	0	16	-10 +80 °C	NBR	
1301-KDNB016-018	1/4"	1,8	0	16	-10 +80 °C	NBR	
1301-KDNB016-020	1/4"	2	0	16	-10 +80 °C	NBR	
1301-KDVB016-020	1/4"	2	0	16	-10 +150 °C	FKM	



Genel Maksat - Ø13 Armatür

Normalde Kapalı 2/2

Sipariş Kodu	Ölçü	Orif. (mm)	Basınç (Bar)		Sıcaklık	Conta/Diyaf.	
			P Min	P Max			
1311-KDNB016-025	1/4"	2,5	0	16	-10 +80 °C	NBR	
1311-KDNB010-030	1/4"	3	0	10	-10 +80 °C	NBR	
1311-KDNB006-040	1/4"	4	0	6	-10 +80 °C	NBR	

Genel Maksat - Ø13 Armatür

Normalde Açık 2/2

Sipariş Kodu	Ölçü	Orif. (mm)	Basınç (Bar)		Sıcaklık	Conta/Diyaf.	
			P Min	P Max			
1311-ADNB016-015	1/4"	1,5	0	16	-10 +80 °C	NBR	
1311-ADNB010-020	1/4"	2	0	16	-10 +80 °C	NBR	
1311-ADVB016-020	1/4"	2	0	16	-10 +80 °C	NBR	



Genel Maksat - Ø9 Armatür

Normalde Kapalı 2/2

Sipariş Kodu	Ölçü	Orif. (mm)	Basınç (Bar)		Sıcaklık	Conta/Diyaf.	
			P Min	P Max			
1302-KDNA010-015	1/8"	1,5	0	10	-10 +80 °C	NBR	
1302-KDNA007-018	1/8"	1,8	0	7	-10 +80 °C	NBR	
1302-KDNA007-020	1/8"	2	0	7	-10 +80 °C	NBR	
1302-KDNB010-015	1/4"	1,5	0	10	-10 +80 °C	NBR	
1302-KDNB007-018	1/4"	1,8	0	7	-10 +80 °C	NBR	
1302-KDNB007-020	1/4"	2	0	7	-10 +80 °C	NBR	



Genel Maksat - Ø13 Armatür

Normalde Kapalı 2/2

Sipariş Kodu	Ölçü	Orif. (mm)	Basınç (Bar)		Sıcaklık	Conta/Diyaf.	
			P Min	P Max			
1312-KDEA007-018	1/8"	1,8	0	7	-10 +140 °C	EPDM	
1312-KDNA007-020	1/8"	2	0	7	-10 +80 °C	NBR	
1312-KDNA003-025	1/8"	2,5	0	3	-10 +80 °C	NBR	
1312-KDEB007-018	1/4"	1,8	0	7	-10 +140 °C	EPDM	
1312-KDNB007-020	1/4"	2	0	7	-10 +80 °C	NBR	
1312-KDNB003-025	1/4"	2,5	0	3	-10 +80 °C	NBR	