


VAKUM VALFLERİ
DİREKT ETKİLİ
Normalde Kapalı 3/2

Sipariş Kodu	Ölçü	Orif. (mm)	Basınç (Bar)		Sıcaklık	Conta/Diyaf.	
			P Min	P Max			
1502-KDNA001-025	1/8"	2,5	-1	1	-10 +80 °C	NBR	
1502-KDNB001-025	1/4"	2,5	-1	1	-10 +80 °C	NBR	


VAKUM VALFLERİ
DİREKT ETKİLİ
Normalde Kapalı 2/2

Sipariş Kodu	Ölçü	Orif. (mm)	Basınç (Bar)		Sıcaklık	Conta/Diyaf.	
			P Min	P Max			
1501-KDNB016-020	1/4"	2	-1	16	-10 +80 °C	NBR	
1501-KDNB010-030		3	-1	10	-10 +80 °C	NBR	
1501-KDNB010-040		4	-1	10	-10 +80 °C	NBR	
1501-KDNC006-050	3/8"	5	-1	6	-10 +80 °C	NBR	
1501-KDNC005-060		6	-1	5	-10 +80 °C	NBR	
1501-KDND006-050	1/2"	5	-1	6	-10 +80 °C	NBR	
1501-KDND005-060		6	-1	5	-10 +80 °C	NBR	
1501-KDND1P5-080		8	-1	1,5	-10 +80 °C	NBR	

Normalde Açık 2/2

1501-ADNB016-020	1/4"	2	-1	16	-10 +80 °C	NBR	
1501-ADNB010-030		3	-1	10	-10 +80 °C	NBR	
1501-ADNB010-040		4	-1	10	-10 +80 °C	NBR	

VAKUM VALFLERİ
SIFIR FARK BASINÇLI -DİYAĞRAMLI
Normalde Kapalı 2/2

Sipariş Kodu	Ölçü	Orif. (mm)	Basınç (Bar)		Sıcaklık	Conta/Diyaf.	
			P Min	P Max			
1501-KHNC010-150	3/8"	15	0	10	-10 +80 °C	NBR	
1501-KHND010-150	1/2"	15	0	10	-10 +80 °C	NBR	
1501-KHNE010-200	3/4"	20	0	10	-10 +80 °C	NBR	
1501-KHNF010-250	1	25	0	10	-10 +80 °C	NBR	

SIFIR FARK BASINÇLI -DİYAĞRAMLI
Normalde Açık 2/2

Sipariş Kodu	Ölçü	Orif. (mm)	Basınç (Bar)		Sıcaklık	Conta/Diyaf.	
			P Min	P Max			
1501-AHNC010-150	3/8"	15	0	10	-10 +80 °C	NBR	
1501-AHND010-150	1/2"	15	0	10	-10 +80 °C	NBR	
1501-AHNE010-200	3/4"	20	0	10	-10 +80 °C	NBR	
1501-AHNF010-250	1	25	0	10	-10 +80 °C	NBR	


SOLENOİD KİLİT

Sipariş Kodu	Mil çapı	Stroke	
6671-KD00000-000	Ø 9	10 mm	