



Yüksek Basınç

Normalde Kapalı 2/2

Sipariş Kodu	Ölçü	Orif. (mm)	Basınç (Bar)		Sıcaklık	Conta/Diyaf.	
			P Min	P Max			
1901-KDNA040-015	1/8"	1,5	0	40	-10 +80 °C	NBR	
1901-KDNA040-018		1,8	0	40	-10 +80 °C	NBR	
1901-KDNA040-020		2	0	40	-10 +80 °C	NBR	
1901-KDNA025-025		2,5	0	25	-10 +80 °C	NBR	
1901-KDEA040-015		1,5	0	40	-10 +140 °C	EPDM	
1901-KDEA040-018		1,8	0	40	-10 +140 °C	EPDM	
1901-KDNA040-020		2	0	40	-10 +140 °C	EPDM	
1901-KDEA025-025		2,5	0	25	-10 +140 °C	EPDM	
1801-KDPA070-015	1/4"	1,5	0	70	-10 +160 °C	PTFE	
1901-KDNB025-015		1,5	0	25	-10 +80 °C	NBR	
1901-KDNB040-015		1,5	0	40	-10 +80 °C	NBR	
1901-KDNB040-018		1,8	0	40	-10 +80 °C	NBR	
1901-KDNB040-020		2	0	40	-10 +80 °C	NBR	
1901-KDNB025-025		2	0	25	-10 +80 °C	NBR	
1901-KDVB030-020		2	0	30	-10 +150 °C	FKM	
1901-KDVB050-015		1,5	0	50	-10 +150 °C	FKM	
1901-KDVB040-020		2	0	40	-10 +150 °C	FKM	
1901-KDVB025-025		2,5	0	25	-10 +150 °C	FKM	
1801-KDPB070-015		1,5	0	70	-10 +160 °C	PTFE	
1801-KDPB100-010		1	0	100	-10 +160 °C	PTFE	
1801-KDPB100-012		1,2	0	100	-10 +160 °C	PTFE	
1801-KDRB100-010		1	0	100	-10 +150 °C	RUBY	

Normalde Açık 2/2

1901-ADNB040-012	1/4"	1,2	0	40	-10 +80 °C	NBR	
1901-ADNB040-015		1,5	0	40	-10 +80 °C	NBR	
1801-ADPB070-012		1,2	0	70	-10 +160 °C	PTFE	
1801-ADRB070-010		1	0	70	-10 +150 °C	RUBY	

Yüksek Basınç-Takviyeli Diyafram

Normalde Kapalı 2/2

1901-KBNC040-120	3/8"	10	0,5	40	-10 +80 °C	NBR	
1901-KBNB040-120	1/4"	12	0,5	40	-10 +80 °C	NBR	
1901-KBND040-120	1/2"	12	0,5	40	-10 +80 °C	NBR	
1901-KBVD040-120		12	0,5	40	-10 +150 °C	FKM	

Normalde Açık 2/2

1901-ABNC040-120	3/8"	10	0,5	40	-10 +80 °C	NBR	
1901-ABND040-120	1/2"	12	0,5	40	-10 +80 °C	NBR	
1901-ABVD040-120		12	0,5	40	-10 +150 °C	FKM	

" 100 bar"

Normalde Kapalı 2/2

1901-KBPD100-120	1/2"	12	0,5	100	-10 +160 °C	PTFE	
------------------	------	----	-----	-----	-------------	------	--

