

Genel Maksat

Normalde Açık 2/2



Sipariş Kodu	Ölçü	Orif. (mm)	Basınç (Bar)		Sıcaklık	Conta/Diyaf.	
			P Min	P Max			
1901-ADNA030-015	1/8"	1,5	0	30	-10 +80 °C	NBR	
1901-ADNA016-020	1/8"	2	0	16	-10 +80 °C	NBR	
1901-ADEA016-015	1/8"	1,5	0	16	-10 +140 °C	EPDM	
1901-ADVA016-020	1/8"	2	0	16	-10 +150 °C	FKM	
1901-ADNB016-020	1/4"	2	0	16	-10 +80 °C	NBR	
1901-ADNB003-030	1/4"	3	0	3	-10 +80 °C	NBR	
1901-ADNB1P5-040	1/4"	4	0	1,5	-10 +80 °C	NBR	
1901-ADVB016-018	1/4"	1,8	0	16	-10 +150 °C	FKM	
1901-ADVB016-020	1/4"	2	0	16	-10 +150 °C	FKM	
1901-ADVB010-025	1/4"	2,5	0	10	-10 +150 °C	FKM	
1901-ADEB003-030	1/4"	3	0	3	-10 +140 °C	EPDM	
1901-ADEB016-018	1/4"	1,8	0	16	-10 +140 °C	EPDM	
1901-ADEB016-020	1/4"	2	0	16	-10 +140 °C	EPDM	
1901-ADVB003-030	1/4"	3	0	3	-10 +150 °C	FKM	
1901-ADVB1P5-040	1/4"	4	0	1,5	-10 +150 °C	FKM	
1901-ADPB010-025	1/4"	2,5	0	10	-10 +160 °C	PTFE	