


Genel Maksat
Normalde Kapalı 2/2

Sipariş Kodu	Ölçü	Orif. (mm)	Basınç (Bar)		Sıcaklık	Conta/Diyaf.	
			P Min	P Max			
1901-KBNB016-080	1/4"	8	0,5	16	-10 +80 °C	NBR	
1901-KBHB016-080		8	0,5	16	-10 +120 °C	HNBR	
1901-KBEB016-080		8	0,5	16	-10 +140 °C	EPDM	
1901-KBVB016-080		8	0,5	16	-10 +150 °C	FKM	
1901-KBNC016-100	3/8"	10	0,5	16	-10 +80 °C	NBR	
1901-KBHC016-100		10	0,5	16	-10 +120 °C	HNBR	
1901-KBEC016-100		10	0,5	16	-10 +140 °C	EPDM	
1901-KBVC016-100		10	0,5	16	-10 +150 °C	FKM	
1901-KBND016-120	1/2"	12	0,5	16	-10 +80 °C	NBR	
1901-KBHD016-120		12	0,5	16	-10 +120 °C	HNBR	
1901-KBED016-120		12	0,5	16	-10 +140 °C	EPDM	
1901-KBVD016-120		12	0,5	16	-10 +150 °C	FKM	
1901-KBEE016-190	3/4"	19	0,5	16	-10 +140 °C	EPDM	
1901-KBNE016-190		19	0,5	16	-10 +80 °C	NBR	
1901-KBHE016-190		19	0,5	16	-10 +120 °C	HNBR	
1901-KBVE016-190		19	0,5	16	-10 +150 °C	FKM	
1901-KBNF016-250	1"	25	0,5	16	-10 +80 °C	NBR	
1901-KBNF016-190		19	0,5	16	-10 +80 °C	NBR	
1901-KBHF016-250		25	0,5	16	-10 +120 °C	HNBR	
1901-KBEF016-250		25	0,5	16	-10 +140 °C	EPDM	
1901-KBVF016-250	1 1/4"	25	0,5	16	-10 +150 °C	FKM	
1901-KBNG010-320		32	0,5	10	-10 +80 °C	NBR	
1901-KBEG010-320		32	0,5	10	-10 +140 °C	EPDM	
1901-KBVG010-320		32	0,5	10	-10 +150 °C	FKM	
1901-KBNH010-400	1 1/2"	40	0,5	10	-10 +80 °C	NBR	
1901-KBEH010-400		40	0,5	10	-10 +140 °C	EPDM	
1901-KBVH010-400		40	0,5	10	-10 +150 °C	FKM	
1901-KBNI010-500	2"	50	0,5	10	-10 +80 °C	NBR	
1901-KBEI010-500		50	0,5	10	-10 +150 °C	EPDM	
1901-KBVI010-500		50	0,5	10	-10 +150 °C	FKM	

Ekonomik Seri

Normalde Kapalı 2/2



Sipariş Kodu	Ölçü	Orif. (mm)	Basınç (Bar)		Sıcaklık	Conta/Diyaf.	
			P Min	P Max			
1931-KDNA016-015	1/8"	1,5	0	16	-10 +80 °C	NBR	
1931-KDVA016-020		2	0	16	-10 +150 °C	FKM	
1931-KDNA010-025		2,5	0	10	-10 +80 °C	NBR	
1931-KDNA016-020		2	0	16	-10 +80 °C	NBR	
1931-KDVA010-020		2	0	10	-10 +150 °C	FKM	
1931-KDEA010-020		2	0	10	-10 +140 °C	EPDM	
1931-KDNB016-015	1/4"	1,5	0	16	-10 +80 °C	NBR	
1931-KDNB016-020		2	0	16	-10 +80 °C	NBR	
1931-KDNB010-025		2,5	0	10	-10 +80 °C	NBR	
1931-KDVB016-020		2	0	16	-10 +150 °C	FKM	
1931-KBNC016-100	3/8"	10	0,5	10	-10 +80 °C	NBR	
1931-KBND016-120	1/2"	12	0,5	16	-10 +80 °C	NBR	
1931-KBED016-120		12	0,5	16	-10 +140 °C	EPDM	
1931-KBNE016-190	3/4"	19	0,5	16	-10 +80 °C	NBR	
1931-KBEE016-190		19	0,5	16	-10 +140 °C	EPDM	
1931-KBNF016-250		25	0,5	16	-10 +80 °C	NBR	
1931-KBNF016-190	1"	19	0,5	16	-10 +80 °C	NBR	
1931-KBVF016-250		25	0,5	16	-10 +150 °C	FKM	
1931-KBEF016-250		25	0,5	16	-10 +140 °C	EPDM	



Tam Geçiş 1/4" Solenoid Valf

Normalde Kapalı 2/2

Sipariş Kodu	Ölçü	Orif. (mm)	Basınç (Bar)		Sıcaklık	Conta/Diyaf.	
			P Min	P Max			
1901-KBNB016-080		8	0,5	16	-10 +80 °C	NBR	
1901-KBHB016-080		8	0,5	16	-10 +120 °C	HNBR	
1901-KBVB016-080		8	0,5	16	-10 +150 °C	FKM	
1901-KBEB016-080		8	0,5	16	-10 +140 °C	EPDM	



Tam Geçiş 1/4" Solenoid Valf

Normalde Açık 2/2

Sipariş Kodu	Ölçü	Orif. (mm)	Basınç (Bar)		Sıcaklık	Conta/Diyaf.	
			P Min	P Max			
1901-ABNB016-080	1/4"	8	0,5	16	-10 +80 °C	NBR	
1901-ABHB016-080	1/4"	8	0,5	16	-10 +150 °C	HNBR	