



Genel Maksat

Normalde Kapalı 2/2

Sipariş Kodu	Ölçü	Orif. (mm)	Basınç (Bar)		Sıcaklık	Conta/Diyaf.	
			P Min	P Max			
1901-KDNA016-015	1/8"	1,5	0	16	-10 +80 °C	NBR	
1901-KDNA016-018	1/8"	1,8	0	16	-10 +80 °C	NBR	
1901-KDNA016-020	1/8"	2	0	16	-10 +80 °C	NBR	
1901-KDNA016-025	1/8"	2,5	0	16	-10 +80 °C	NBR	
1901-KDNA010-030	1/8"	3	0	10	-10 +80 °C	NBR	
1901-KDNA006-040	1/8"	4	0	6	-10 +80 °C	NBR	
1901-KDEA016-015	1/8"	1,5	0	16	-10 +140 °C	EPDM	
1901-KDEA016-018	1/8"	1,8	0	16	-10 +140 °C	EPDM	
1901-KDVA016-020	1/8"	2	0	16	-10 +150 °C	FKM	
1901-KDVA010-030	1/8"	3	0	10	-10 +150 °C	FKM	
1901-KDNB016-015	1/4"	1,5	0	16	-10 +80 °C	NBR	
1901-KDNB016-018	1/4"	1,8	0	16	-10 +80 °C	NBR	
1901-KDNB016-020	1/4"	2	0	16	-10 +80 °C	NBR	
1901-KDNB016-025	1/4"	2,5	0	16	-10 +80 °C	NBR	
1901-KDNB010-030	1/4"	3	0	10	-10 +80 °C	NBR	
1901-KDNB010-040	1/4"	4	0	10	-10 +80 °C	NBR	
1901-KDEB016-015	1/4"	1,5	0	16	-10 +140 °C	EPDM	
1901-KDEB016-018	1/4"	1,8	0	16	-10 +140 °C	EPDM	
1901-KDEB016-020	1/4"	2	0	16	-10 +140 °C	EPDM	
1901-KDEB010-030	1/4"	3	0	10	-10 +140 °C	EPDM	
1901-KDVB016-015	1/4"	1,5	0	16	-10 +150 °C	FKM	
1901-KDVB016-018	1/4"	1,8	0	16	-10 +150 °C	PTFE	
1901-KDVB016-020	1/4"	2	0	16	-10 +150 °C	FKM	
1901-KDVB010-030	1/4"	3	0	10	-10 +150 °C	FKM	
1901-KDVB006-040	1/4"	4	0	6	-10 +150 °C	FKM	
1901-KDPB016-020	1/4"	2	0	16	-10 +160 °C	PTFE	
1901-KDPB010-030	1/4"	3	0	10	-10 +160 °C	PTFE	
1901-KDPB006-040	1/4"	4	0	6	-10 +160 °C	PTFE	