



YENİ ÜRÜN
YENİ ÜRÜN
YENİ ÜRÜN
YENİ ÜRÜN
YENİ ÜRÜN
YENİ ÜRÜN

Sıfır Basınç-Diyafram Kontrollü-HUNG Tipi Δ **Normalde Kapalı 2/2**

Sipariş Kodu	Ölçü	Orif. (mm)	Basınç (Bar)		Sıcaklık	Conta/Diyaf.	
			P Min	P Max			
1901-KHNC010-150	3/8"	15	0	10	-10 +80 °C	NBR	
1901-KHND010-150	1/2"	15	0	10	-10 +80 °C	NBR	
1901-KHED006-150		15	0	6	-10 +140 °C	EPDM	
1901-KHVD010-150	3/4"	15	0	10	-10 +150 °C	FKM	
1901-KHNE010-200		20	0	10	-10 +80 °C	NBR	
1901-KHEE006-200		20	0	6	-10 +140 °C	EPDM	
1901-KHVE010-200	1"	20	0	10	-10 +150 °C	FKM	
1901-KHEF006-250		25	0	6	-10 +140 °C	EPDM	
1901-KHNF010-250	1"	25	0	10	-10 +80 °C	NBR	
1901-KHVF010-250		25	0	10	-10 +150 °C	FKM	
1901-KHNG010-320	1 1/4"	32	0	10	-10 +80 °C	NBR	
1901-KHVG010-320	1 1/2"	32	0	10	-10 +150 °C	FKM	
1901-KHNH010-400		40	0	10	-10 +80 °C	NBR	
1901-KHVG008-400	2"	40	0	8	-10 +150 °C	FKM	
1901-KHNI010-500		50	0	10	-10 +80 °C	NBR	
1901-KHVI010-500		50	0	10	-10 +150 °C	FKM	


Sıfır Basınç-Diyafram Kontrollü-HUNG Tipi **Normalde Açık 2/2**

Sipariş Kodu	Ölçü	Orif. (mm)	Basınç (Bar)		Sıcaklık	Conta/Diyaf.	
			P Min	P Max			
1901-AHNC010-150	3/8"	15	0	10	-10 +80 °C	NBR	
1901-AHND010-150	1/2"	15	0	10	-10 +80 °C	NBR	
1901-AHED006-150		15	0	6	-10 +140 °C	EPDM	
1901-AHVD010-150	3/4"	15	0	10	-10 +150 °C	VITON	
1901-AHNE010-200		20	0	10	-10 +80 °C	NBR	
1901-AHEE006-200		20	0	6	-10 +140 °C	EPDM	
1901-AHNF010-250	1"	25	0	10	-10 +80 °C	NBR	
1901-AHEF006-250		25	0	6	-10 +140 °C	EPDM	