

3/2 SOLENOID VALF
Normalde Kapalı 2/2

Sipariş Kodu	Ölçü	Orif. (mm)	Basınç (Bar)		Sıcaklık	Conta/Diyaf.	
			P Min	P Max			
1902-KDNA010-015	1/8"	1,5	0	10	-10 +80 °C	NBR	
1902-KDVA010-015		1,5	0	10	-10 +150 °C	FKM	
1902-KDVA007-018		1,8	0	7	-10 +150 °C	FKM	
1902-KDVA003-025		2,5	0	3	-10 +150 °C	FKM	
1902-KDNA007-018		1,8	0	7	-10 +80 °C	NBR	
1902-KDVA007-020		2	0	7	-10 +150 °C	FKM	
1902-KDNA007-020		2	0	7	-10 +80 °C	NBR	
1902-KDNA003-025		2,5	0	3	-10 +80 °C	NBR	
1902-KDNB010-015	1/4"	1,5	0	10	-10 +80 °C	NBR	
1902-KDNB007-018		1,8	0	7	-10 +80 °C	NBR	
1902-KDNB007-020		2	0	7	-10 +80 °C	NBR	
1902-KDNB003-025		2,5	0	3	-10 +80 °C	NBR	
1902-KDVB010-015		1,5	0	10	-10 +150 °C	FKM	
1902-KDVB007-018		1,8	0	7	-10 +150 °C	FKM	
1902-KDVB007-020		2	0	7	-10 +150 °C	FKM	
1902-KDVB003-025		2,5	0	3	-10 +150 °C	FKM	

3/2 SOLENOID VALF
Normalde Açık 3/2

1902-ADNA006-015	1/8"	1,5	0	6	-10 +80 °C	NBR	
1902-ADVA006-018		1,8	0	6	-10 +150 °C	FKM	
1902-ADNB006-020	1/4"	2	0	6	-10 +80 °C	NBR	

3/2 SOLENOID VALF (Ø13 Armatur)
Normalde Kapalı 3/2

Sipariş Kodu	Ölçü	Orif. (mm)	Basınç (Bar)		Sıcaklık	Conta/Diyaf.	
			P Min	P Max			
1312-KDEA007-018	1/8"	1,8	0	7	-10 +140 °C	EPDM	
1312-KDNA007-020	1/8"	2	0	7	-10 +80 °C	NBR	
1312-KDNA003-025	1/8"	2,5	0	3	-10 +80 °C	NBR	
1312-KDEB007-018	1/4"	1,8	0	7	-10 +140 °C	EPDM	
1312-KDNB007-020	1/4"	2	0	7	-10 +80 °C	NBR	
1312-KDNB003-025	1/4"	2,5	0	3	-10 +80 °C	NBR	

3/2 SOLENOID VALF (Ø9 Armatur)
Normalde Kapalı 3/2

Sipariş Kodu	Ölçü	Orif. (mm)	Basınç (Bar)		Sıcaklık	Conta/Diyaf.	
			P Min	P Max			
1302-KDNA010-015	1/8"	1,5	0	10	-10 +80 °C	NBR	
1302-KDNA007-018		1,8	0	7	-10 +80 °C	NBR	
1302-KDNA007-020		2	0	7	-10 +80 °C	NBR	
1302-KDNB010-015	1/4"	1,5	0	10	-10 +80 °C	NBR	
1302-KDNB007-018		1,8	0	7	-10 +80 °C	NBR	
1302-KDNB007-020		2	0	7	-10 +80 °C	NBR	