

**Ekonomik Seri**
**Normalde Kapalı 2/2**


| Sipariş Kodu            | Ölçü | Orif. (mm) | Basınç (Bar) |           | Sıcaklık          | Conta/Diyaf. |  |
|-------------------------|------|------------|--------------|-----------|-------------------|--------------|--|
|                         |      |            | P Min        | P Max     |                   |              |  |
| 1931-KDNA016-015        | 1/8" | 1,5        | 0            | 16        | -10 +80 °C        | NBR          |  |
| 1931-KDVA016-020        |      | 2          | 0            | 16        | -10 +150 °C       | FKM          |  |
| 1931-KDNA010-025        |      | 2,5        | 0            | 10        | -10 +80 °C        | NBR          |  |
| 1931-KDNA016-020        |      | 2          | 0            | 16        | -10 +80 °C        | NBR          |  |
| 1931-KDVA010-020        |      | 2          | 0            | 10        | -10 +150 °C       | FKM          |  |
| 1931-KDEA010-020        |      | 2          | 0            | 10        | -10 +140 °C       | EPDM         |  |
| 1931-KDNB016-015        | 1/4" | 1,5        | 0            | 16        | -10 +80 °C        | NBR          |  |
| 1931-KDNB016-020        |      | 2          | 0            | 16        | -10 +80 °C        | NBR          |  |
| 1931-KDNB010-025        |      | 2,5        | 0            | 10        | -10 +80 °C        | NBR          |  |
| 1931-KDVB016-020        |      | 2          | 0            | 16        | -10 +150 °C       | FKM          |  |
| 1931-KBNC016-100        | 3/8" | 10         | 0,5          | 10        | -10 +80 °C        | NBR          |  |
| 1931-KBND016-120        | 1/2" | 12         | 0,5          | 16        | -10 +80 °C        | NBR          |  |
| 1931-KBED016-120        |      | 12         | 0,5          | 16        | -10 +140 °C       | EPDM         |  |
| 1931-KBNE016-190        | 3/4" | 19         | 0,5          | 16        | -10 +80 °C        | NBR          |  |
| 1931-KBEE016-190        |      | 19         | 0,5          | 16        | -10 +140 °C       | EPDM         |  |
| 1931-KBNF016-250        |      | 25         | 0,5          | 16        | -10 +80 °C        | NBR          |  |
| <b>1931-KBNF016-190</b> | 1"   | <b>19</b>  | <b>0,5</b>   | <b>16</b> | <b>-10 +80 °C</b> | <b>NBR</b>   |  |
| 1931-KBVF016-250        |      | 25         | 0,5          | 16        | -10 +150 °C       | FKM          |  |
| 1931-KBEF016-250        |      | 25         | 0,5          | 16        | -10 +140 °C       | EPDM         |  |


**Tam Geçiş 1/4" Solenoid Valf**
**Normalde Kapalı 2/2**

| Sipariş Kodu     | Ölçü | Orif. (mm) | Basınç (Bar) |       | Sıcaklık    | Conta/Diyaf. |  |
|------------------|------|------------|--------------|-------|-------------|--------------|--|
|                  |      |            | P Min        | P Max |             |              |  |
| 1901-KBNB016-080 |      | 8          | 0,5          | 16    | -10 +80 °C  | NBR          |  |
| 1901-KBHB016-080 |      | 8          | 0,5          | 16    | -10 +120 °C | HNBR         |  |
| 1901-KBVB016-080 |      | 8          | 0,5          | 16    | -10 +150 °C | FKM          |  |
| 1901-KBEB016-080 |      | 8          | 0,5          | 16    | -10 +140 °C | EPDM         |  |


**Tam Geçiş 1/4" Solenoid Valf**
**Normalde Açık 2/2**

| Sipariş Kodu     | Ölçü | Orif. (mm) | Basınç (Bar) |       | Sıcaklık    | Conta/Diyaf. |  |
|------------------|------|------------|--------------|-------|-------------|--------------|--|
|                  |      |            | P Min        | P Max |             |              |  |
| 1901-ABNB016-080 | 1/4" | 8          | 0,5          | 16    | -10 +80 °C  | NBR          |  |
| 1901-ABHB016-080 | 1/4" | 8          | 0,5          | 16    | -10 +150 °C | HNBR         |  |