


Direkt Etkili
Normalde Kapalı 2/2

Sipariş Kodu	Ölçü	Orif. (mm)	Basınç (Bar)		Sıcaklık	Conta/Diyaf.	
			P Min	P Max			
1901-KDNB005-060	1/4"	6	0	5	-10 +80 °C	NBR	
1901-KDEB005-060		6	0	5	-10 +140 °C	EPDM	
1901-KDNC006-050	3/8"	5	0	6	-10 +80 °C	NBR	
1901-KDNC005-060		6	0	5	-10 +80 °C	NBR	
1901-KDEC005-060		6	0	5	-10 +140 °C	EPDM	
1901-KDVC006-050		5	0	6	-10 +150 °C	FKM	
1901-KDVC005-060	1/2"	6	0	5	-10 +150 °C	FKM	
1901-KDND010-030		3	0	10	-10 +80 °C	NBR	
1901-KDND006-050		5	0	6	-10 +80 °C	NBR	
1901-KDND005-060		6	0	5	-10 +80 °C	NBR	
1901-KDND1P5-080		8	0	1,5	-10 +80 °C	NBR	
1901-KDED006-050		5	0	6	-10 +140 °C	EPDM	
1901-KDED1P5-080		8	0	1,5	-10 +140 °C	EPDM	
1901-KDVD006-050		5	0	6	-10 +150 °C	FKM	
1901-KDVD005-060		6	0	5	-10 +150 °C	FKM	
1901-KDPD005-060		6	0	5	-10 +160 °C	PTFE	
1901-KDNE006-050		5	0	6	-10 +80 °C	NBR	
1901-KDNE010-030		3	0	10	-10 +80 °C	NBR	
1901-KDNF006-050	1"	5	0	6	-10 +80 °C	NBR	
1901-KDNF010-030		3	0	10	-10 +80 °C	NBR	

Direkt Etkili 3/8" & 1/2"
Normalde Açık 2/2

Sipariş Kodu	Ölçü	Orif. (mm)	Basınç (Bar)		Sıcaklık	Conta/Diyaf.	
			P Min	P Max			
1901-ADNC001-050	3/8"	5	0	1	-10 +80 °C	NBR	
1901-ADND001-050	1/2"	5	0	1	-10 +80 °C	NBR	
1901-ADVC001-050	3/8"	5	0	1	-10 +150 °C	FKM	
1901-ADVD001-050	1/2"	5	0	1	-10 +150 °C	FKM	
1901-ADED001-050		5	0	1	-10 +140 °C	EPDM	

Direkt Etkili - Gaz için
Normalde Kapalı 2/2

3901A-KDND005-060	1/2"	6	0	5	-10 +80 °C	NBR	
3901A-KDND006-050		5	0	6	-10 +80 °C	NBR	
3901A-KDND1P5-080		8	0	1,5	-10 +80 °C	NBR	
3901A-KDED1P5-080		8	0	1,5	-10 +140 °C	EPDM	


Debi Ayarlı
Normalde Kapalı 2/2

Sipariş Kodu	Ölçü	Orif. (mm)	Basınç (Bar)		Sıcaklık	Conta/Diyaf.	
			P Min	P Max			
1941-KDNB010-030	1/4"	3	0	10	-10 +80 °C	NBR	