

**Buhar Solenoid Valfleri****Normalde Kapalı 2/2**

Sipariş Kodu	Ölçü	Orif. (mm)	Basınç (Bar)		Sıcaklık	Conta/Diyaf.	
			P Min	P Max			
4901-KDEA006-015	1/8"	1,5	0	6	-10 +140 °C	EPDM	
4901-KDEA006-018		1,8	0	6	-10 +140 °C	EPDM	
4901-KDEA006-020		2	0	6	-10 +140 °C	EPDM	
4901-KDEA006-025		2,5	0	6	-10 +140 °C	EPDM	
4901-KDEA006-030		3	0	6	-10 +140 °C	EPDM	
4901-KDEA006-040		4	0	6	-10 +140 °C	EPDM	
4901-KDEB006-015	1/4"	1,5	0	6	-10 +140 °C	EPDM	
4901-KDEB006-018		1,8	0	6	-10 +140 °C	EPDM	
4901-KDEB006-020		2	0	6	-10 +140 °C	EPDM	
4901-KDEB006-025		2,5	0	6	-10 +140 °C	EPDM	
4901-KDEB006-030		3	0	6	-10 +140 °C	EPDM	
4901-KDEB006-040		4	0	6	-10 +140 °C	EPDM	

**Buhar Solenoid Valfleri****Normalde Kapalı 2/2**

Sipariş Kodu	Ölçü	Orif. (mm)	Basınç (Bar)		Sıcaklık	Conta/Diyaf.	
			P Min	P Max			
4901-KDPA010-020	1/8"	2	0	10	-10 +160 °C	PTFE	
4901-KDPB010-020	1/4"	2	0	10	-10 +160 °C	PTFE	
4901-KDPB006-030		3	0	6	-10 +160 °C	PTFE	
4901-KDPB006-040		4	0	6	-10 +160 °C	PTFE	

**Buhar Solenoid Valfleri****Normalde Kapalı 2/2**

Sipariş Kodu	Ölçü	Orif. (mm)	Basınç (Bar)		Sıcaklık	Conta/Diyaf.	
			P Min	P Max			
4901-KDEC006-050	3/8"	5	0	6	-10 +140 °C	EPDM	
4901-KDED006-050	1/2"	5	0	6	-10 +140 °C	EPDM	
4901-KDED005-060		6	0	5	-10 +140 °C	EPDM	
4901-KDPC006-050	3/8"	6	0	5	-10 +160 °C	PTFE	
4901-KDPD006-050	1/2"	6	0	5	-10 +160 °C	PTFE	

**Buhar Solenoid Valfleri****Normalde Açık 2/2**

Sipariş Kodu	Ölçü	Orif. (mm)	Basınç (Bar)		Sıcaklık	Conta/Diyaf.	
			P Min	P Max			
4901-ADEA006-020	1/8"	2	0	6	-10 +140 °C	EPDM	
4901-ADEB006-020	1/4"	2	0	6	-10 +140 °C	EPDM	