

Exproof Bobinli Solenoid Valfler
Normalde Kapalı 2/2


Sipariş Kodu	Ölçü	Orif. (mm)	Basınç (Bar)		Sıcaklık	Conta/Diyaf.	
			P Min	P Max			
5801-KDNA016-012	1/8"	1,2	0	16	-10 +80 °C	NBR	
5801-KDNA008-020		2	0	8	-10 +80 °C	NBR	
5801-KDNB016-012	1/4"	1,2	0	16	-10 +80 °C	NBR	
5801-KDNB008-020		2	0	8	-10 +80 °C	NBR	
5801-KBNC010-100	3/8"	10	0,5	10	-10 +80 °C	NBR	
5801-KBND010-120	1/2"	12	0,5	10	-10 +80 °C	NBR	
5801-KBVD010-120		12	0,5	10	-10 +150 °C	FKM	
5801-KBNE010-190	3/4"	19	0,5	10	-10 +80 °C	NBR	
5801-KBNF010-250	1"	25	0,5	10	-10 +80 °C	NBR	
5801-KBNG003-320	1 1/4"	32	0,5	3	-10 +80 °C	NBR	
5801-KBNH003-400	1 1/2"	40	0,5	3	-10 +80 °C	NBR	
5801-KBNI003-500	2"	50	0,5	3	-10 +80 °C	NBR	

Exproof Bobinli Solenoid Valfler
Normalde Kapalı 2/2


Sipariş Kodu	Ölçü	Orif. (mm)	Basınç (Bar)		Sıcaklık	Conta/Diyaf.	
			P Min	P Max			
5901-KDNA016-020	1/8"	2	0	16	-10 +80 °C	NBR	
5901-KDNB016-020	1/4"	2	0	16	-10 +80 °C	NBR	
5901-KDVB016-025		2,5	0	16	-10 +150 °C	FKM	
5901-KDND016-020	1/2"	2	0	16	-10 +80 °C	NBR	
5901-KBNC016-100	3/8"	10	0	16	-10 +80 °C	NBR	
5901-KBND016-120	1/2"	12	0	16	-10 +80 °C	NBR	
5901-KBNE016-190	3/4"	19	0	16	-10 +80 °C	NBR	
5901-KBNF016-250	1"	25	0	16	-10 +80 °C	NBR	
5901-KBVF016-250		25	0	16	-10 +150 °C	FKM	
5901-KBNG010-320	1 1/4"	32	0	10	-10 +80 °C	NBR	
5901-KBVG010-320		32	0	10	-10 +150 °C	FKM	
5901-KBNH010-400	1 1/2"	40	0	10	-10 +80 °C	NBR	
5901-KBVH010-400		40	0	10	-10 +150 °C	FKM	
5901-KBNI010-500	2"	50	0	10	-10 +80 °C	NBR	
5901-KBVI010-500		50	0	10	-10 +150 °C	FKM	