


Paslanmaz Solenoid Valf
Normalde Kapalı 2/2

Sipariş Kodu	Ölçü	Orif. (mm)	Basınç (Bar)		Sıcaklık	Conta/Diyaf.	
			P Min	P Max			
7901-KDPA016-020	1/8"	2	0	16	-10 +160 °C	PTFE	
7901-KDEA016-020		2	0	16	-10 +140 °C	EPDM	
7901-KDNA016-020		2	0	16	-10 +80 °C	NBR	
7901-KDVA016-020		2	0	16	-10 +150 °C	FKM	
7901-KDPB016-020	1/4"	2	0	16	-10 +160 °C	PTFE	
7901-KDPB010-030		3	0	10	-10 +160 °C	PTFE	
7901-KDNB016-020		2	0	16	-10 +80 °C	NBR	
7901-KDVB016-020		2	0	16	-10 +150 °C	FKM	
7901-KDVB010-030	3/8"	3	0	10	-10 +150 °C	FKM	
7901-KDVC006-050		5	0	6	-10 +150 °C	FKM	
7901-KDVC005-060		6	0	5	-10 +150 °C	FKM	
7901-KDPC006-050		5	0	6	-10 +160 °C	PTFE	
7901-KDVC005-060	1/2"	6	0	5	-10 +150 °C	FKM	
7901-KDPC005-060		6	0	5	-10 +160 °C	PTFE	
7901-KDNC006-050		5	0	6	-10 +80 °C	NBR	
7901-KDEC006-050		5	0	6	-10 +140 °C	EPDM	
7901-KDVD006-050	3/4"	5	0	6	-10 +150 °C	FKM	
7901-KDPD006-050		5	0	6	-10 +160 °C	PTFE	
7901-KDVD005-060		6	0	5	-10 +150 °C	FKM	
7901-KDPD005-060		6	0	5	-10 +160 °C	PTFE	
7901-KDND005-060	1"	6	0	5	-10 +80 °C	NBR	
7901-KDND1P5-080		8	0	1,5	-10 +80 °C	NBR	
7901-KDVD1P5-080		8	0	1,5	-10 +150 °C	FKM	
7901-KDPE005-060		6	0	5	-10 +160 °C	PTFE	
7901-KDEE005-060	1"	6	0	5	-10 +140 °C	EPDM	
7901-KDNE005-060		6	0	5	-10 +80 °C	NBR	
7901-KDNF005-060		6	0	5	-10 +80 °C	NBR	
7901-KDPF005-060		6	0	5	-10 +160 °C	PTFE	

Asit Uygulamaları İçin Paslanmaz
Solenoid Valf
Normalde Kapalı 2/2

Sipariş Kodu	Ölçü	Orif. (mm)	Basınç (Bar)		Sıcaklık	Conta/Diyaf.	
			P Min	P Max			
7911-KDPA016-020	1/8"	2	0	16	-10 +160 °C	PTFE	
7911-KDPB016-020	1/4"	2	0	16	-10 +160 °C	PTFE	
7911-KDVD006-050	1/2"	5	0	6	-10 +150 °C	FKM	

Paslanmaz Solenoid Valf
Normalde Açık 2/2

Sipariş Kodu	Ölçü	Orif. (mm)	Basınç (Bar)		Sıcaklık	Conta/Diyaf.	
			P Min	P Max			
7901-ADV016-020	1/4"	2	0	16	-10 +150 °C	FKM	
7901-ADND001-050	1/2"	5	0	1	-10 +80 °C	NBR	