


Grup Valf - Manuel Kumandalı
Tekli - Normalde Kapalı 2/2

Sipariş Kodu	Ölçü	Orif. (mm)	Basınç (Bar)		Sıcaklık	Conta/Diyaf.	
			P Min	P Max			
8911-KDNA016-020	1/8"	2	0	16	-10 +80 °C	NBR	
8911-KDNB016-020	1/4"	2	0	16	-10 +80 °C	NBR	
8911-KDVB016-020		2	0	16	-10 +150 °C	FKM	

Üçlü - Normalde Kapalı 2/2

8931-KDNA016-020	1/8"	2	0	16	-10 +80 °C	NBR	
8931-KDNB016-020	1/4"	2	0	16	-10 +80 °C	NBR	


Grup Valf - Manuel Kumandalı
Tekli - Normalde Kapalı 3/2

Sipariş Kodu	Ölçü	Orif. (mm)	Basınç (Bar)		Sıcaklık	Conta/Diyaf.	
			P Min	P Max			
8912-KDNA010-015	1/8"	1,5	0	10	-10 +80 °C	NBR	
8912-KDNA007-020		2	0	7	-10 +80 °C	NBR	
8912-KDNA010-020		2	0	10	-10 +80 °C	NBR	
8912-KDNB010-015	1/4"	1,5	0	10	-10 +80 °C	NBR	
8912-KDNB007-020		2	0	7	-10 +80 °C	NBR	
8912-KDNB010-020		2	0	10	-10 +80 °C	NBR	

Grup Valf - Manuel Kumandalı
Üçlü - Normalde Kapalı 3/2

8932-KDNA010-015	1/8"	1,5	0	10	-10 +80 °C	NBR	
8932-KDNA007-020		2	0	7	-10 +80 °C	NBR	
8932-KDNA010-020		2	0	10	-10 +80 °C	NBR	
8932-KDNB010-015	1/4"	1,5	0	10	-10 +80 °C	NBR	
8932-KDNB007-020		2	0	7	-10 +80 °C	NBR	
8932-KDNB010-020		2	0	10	-10 +80 °C	NBR	
8932-KDVB007-020		2	0	7	-10 +150 °C	FKM	


Manuel Kumandalı
Normalde Kapalı 2/2

Sipariş Kodu	Ölçü	Orif. (mm)	Basınç (Bar)		Sıcaklık	Conta/Diyaf.	
			P Min	P Max			
8901-KBND016-120	1/2"	12	0,5	16	-10 +80 °C	NBR	
8901-KBVD016-120		12	0,5	16	-10 +150 °C	FKM	
8901-KBNE016-190	3/4"	19	0,5	16	-10 +80 °C	NBR	
8901-KBVE016-190		19	0,5	16	-10 +150 °C	FKM	
8901-KBNF016-250	1"	25	0,5	16	-10 +80 °C	NBR	

Ekonomik Seri Manuel Kumandalı (Ø9 Armatur)
Normalde Kapalı 2/2

Sipariş Kodu	Ölçü	Orif. (mm)	Basınç (Bar)		Sıcaklık	Conta/Diyaf.	
			P Min	P Max			
8941-KBND016-120	1/2"	12	0,5	16	-10 +80 °C	NBR	
8941-KBNE016-190	3/4"	19	0,5	16	-10 +80 °C	NBR	