

ÇELİK TELLİ HİDROLİK HORTUMLAR

FORCESTREAM® R1 A/1ST

SAE 100 R1A/DIN-EN 853 1ST

TS EN 853

Hidrolik yağlara dayanıklı özel sentetik kauçuktan mamul, iş ve tarım makinelerinde yüksek basınç gerektiren hidrolik devrelerde.



İÇ	DÇ	ÇB	PB	KYÇ/r	Ağr
inch	mm	bar	bar	mm	gr/m
3/16"	12.3	250	1100	90	195
1/4"	15.5	225	1030	100	290
5/16"	17.1	215	970	115	335
3/8"	19.4	180	820	130	410
1/2"	22.6	160	700	180	505
5/8"	25.8	130	600	200	585
3/4"	29.8	105	480	240	720
1"	37.6	88	375	300	1035
1 1/4"	45	63	280	420	1340
1 1/2"	51.4	50	260	500	1535
2"	66.4	40	250	630	2275

ULTIMATE 1SN

SAE 100 R1 AT/DIN-EN 853 1SN

TS EN 853 135°C

Yüksek sıcaklıkta hidrolik yağlara dayanıklı özel sentetik kauçuktan mamul, sanayi ve madenlerde yüksek basınç ve sıcaklık gerektiren hidrolik devrelerde.



İÇ	DÇ	ÇB	PB	KYÇ/r	Ağr
inch	mm	bar	bar	mm	gr/m
3/16"	11.6	250	1100	90	190
1/4"	13.2	225	1030	100	235
5/16"	14.8	215	970	115	275
3/8"	17.2	180	820	130	350
1/2"	20.4	160	700	180	435
5/8"	23.5	130	600	200	500
3/4"	27.5	105	500	240	635
1"	35.4	88	375	300	935
1 1/4"	43.5	63	280	420	1310
1 1/2"	50	50	260	500	1485
2"	63.6	40	250	630	2020
2 1/2"	76.5	40	200	760	2670
3"	88.5	35	160	900	2865

FORCESTREAM R1AT/1SN

SAE 100 R1 AT/DIN-EN 853 1SN

TS EN 853

Hidrolik yağlara dayanıklı özel sentetik kauçuktan mamul, iş ve tarım makinelerinde yüksek basınç gerektiren hidrolik devrelerde.



İÇ	DÇ	ÇB	PB	KYÇ/r	Ağr
inch	mm	bar	bar	mm	gr/m
3/16"	11.6	250	1100	90	180
1/4"	13.2	225	1030	100	220
5/16"	14.8	215	970	115	260
3/8"	17.2	180	820	130	330
1/2"	20.4	160	700	180	410
5/8"	23.5	130	600	200	470
3/4"	27.5	105	500	240	585
1"	35.4	88	375	300	870
1 1/4"	43.5	63	280	420	1205
1 1/2"	50	50	260	500	1400
2"	63.6	40	250	630	1910
2 1/2"	76.5	40	200	762	2535
3"	88.5	35	160	900	2710

FORCESTREAM 1SC

DIN-EN 857 1SC

TS EN 857

Hidrolik yağlara dayanıklı özel sentetik kauçuktan mamul, iş ve tarım makinelerinde yüksek basınç gerektiren hidrolik devrelerde.



İÇ	DÇ	ÇB	PB	KYÇ/r	Ağr
inch	mm	bar	bar	mm	gr/m
1/4"	12.2	225	1100	50	180
5/16"	13.6	215	1000	55	200
3/8"	15.5	180	900	60	260
1/2"	19	160	800	70	345
5/8"	22.4	130	650	90	420
3/4"	25.8	105	520	100	495
1"	33.4	88	430	160	735