

SELTEX R6

EN 854 R6 SAE 100 R6

TS EN 854 R6

Hidrolik yağlara dayanıklı özel sentetik kauçuktan mamul, hidrolik kontrollü ünitelerde yüksek basınçlı hidrolik yağ, fuel oil, gres yağı, su ve hava tahliyesinde.



İÇ	DÇ	ÇB	PB	KYÇ/r	Ağr
inch	mm	bar	bar	mm	gr/m
3/16"	10.7	34	250	35	90
1/4"	12.3	28	200	45	105
5/16"	13.9	28	200	65	125
3/8"	15.5	28	200	75	150
1/2"	19.5	28	200	90	225
5/8"	22.6	24	140	115	260
3/4"	25.8	21	130	140	315
1"	33.2	20	100	150	470

ULTIMATE R6

EN 854 R6 SAE 100 R6

TS EN 854 R6 135°C

Yüksek sıcaklıkta hidrolik yağlara dayanıklı özel sentetik kauçuktan mamul, hidrolik kontrollü ünitelerde yüksek basınçlı hidrolik yağ, fuel oil, gres yağı tahliyesinde.



İÇ	DÇ	ÇB	PB	KYÇ/r	Ağr
inch	mm	bar	bar	mm	gr/m
3/16"	10.7	34	250	35	100
1/4"	12.3	28	200	45	120
5/16"	13.9	28	200	65	140
3/8"	15.5	28	200	75	165
1/2"	19.5	28	200	90	245
5/8"	22.6	24	140	115	290
3/4"	25.8	21	130	140	345
1"	33.2	20	100	150	505

SELTEX R3

EN 854 R3 SAE 100 R3

TS EN 854 R3

Hidrolik yağlara dayanıklı özel sentetik kauçuktan mamul, hidrolik kontrollü ünitelerde yüksek basınçlı hidrolik yağ, fuel-oil, gres yağı, su ve hava tahliyesinde.



İÇ	DÇ	ÇB	PB	KYÇ/r	Ağr
inch	mm	bar	bar	mm	gr/m
3/16"	12.7	103	412	80	155
1/4"	14.3	86	400	80	185
5/16"	17.5	83	370	100	270
3/8"	19.1	78	340	100	300
1/2"	23.8	69	300	125	435
5/8"	27	60	270	140	500
3/4"	31.8	52	240	150	695
1"	38.1	39	190	205	865
1 1/4"	44.5	26	140	255	995
1 1/2"	51	20	110	295	1170

SELTEX 1TE

EN 854 1 TE

TS EN 854 1TE

Hidrolik yağlara dayanıklı özel sentetik kauçuktan mamul, hidrolik kontrollü ünitelerde yüksek basınçlı hidrolik yağ, fuel-oil, gres yağı, su ve hava tahliyesinde.



İÇ	DÇ	ÇB	PB	KYÇ/r	Ağr
inch	mm	bar	bar	mm	gr/m
3/16"	10.7	25	230	35	95
1/4"	12.3	25	180	45	115
5/16"	13.9	20	180	65	130
3/8"	15.5	20	170	75	155
1/2"	19	16	160	90	205
5/8"	22.6	16	130	115	265
3/4"	25.8	12	120	140	315
1"	33.2	12	95	150	475