

TEKSTİL ÖRGÜLÜ HİDROLİK HORTUMLAR

SELTEX 2TE

EN 854 2 TE

TS EN 854 2TE

Hidrolik yağlara dayanıklı özel sentetik kauçuktan mamul, hidrolik kontrollü ünitelerde yüksek basınçlı hidrolik yağ, fuel-oil, gres yağı, su ve hava tahliyesinde.



İÇ	DÇ	ÇB	PB	KYÇ/r	Ağr
inch	mm	bar	bar	mm	gr/m
3/16"	11.8	80	410	25	115
1/4"	13.4	75	400	40	150
5/16"	14.9	68	380	50	170
3/8"	16.5	63	310	60	195
1/2"	19.7	58	280	70	240
5/8"	23.9	50	260	90	325
3/4"	27	45	230	110	380
1"	34.4	40	200	150	545
1 1/4"	41.4	35	180	170	740
1 1/2"	48.1	30	180	190	870

SELTEX 3TE

EN 854 3 TE

TS EN 854 3TE

Hidrolik yağlara dayanıklı özel sentetik kauçuktan mamul, hidrolik kontrollü ünitelerde yüksek basınçlı hidrolik yağ, fuel-oil, gres yağı, su ve hava tahliyesinde.



İÇ	DÇ	ÇB	PB	KYÇ/r	Ağr
inch	mm	bar	bar	mm	gr/m
3/16"	12.8	160	700	40	135
1/4"	14.4	145	630	45	165
5/16"	16.9	130	580	55	215
3/8"	18.5	110	500	70	245
1/2"	21.7	93	440	85	305
5/8"	25.9	80	380	105	410
3/4"	29	70	330	130	465
1"	35.9	55	280	150	630
1 1/4"	42.3	45	220	190	755
1 1/2"	49.6	40	190	240	965
2"	62.3	33	160	300	1280
2 3/8"	72	25	140	400	1555

SELTEX R4

SAE J 517 R4

Hidrolik yağlara ve yakıtlara dayanıklı özel sentetik kauçuk, iş ve tarım makinelerinde hidrolik sistemlerin dönüş devrelerinde.



İÇ	DÇ	ÇB	PB	KYÇ/r	Ağr
inch	mm	bar	bar	mm	gr/m
3/4"	32	21	84	125	755
1"	37.4	17	68	150	885
1 1/4"	45	14	56	200	1140
1 1/2"	52	10	40	255	1550
2"	64	7	28	300	1890
2 1/2"	77	4	16	355	2377
3"	90	4	16	460	3121
3 1/2"	103	3	12	590	3416
4"	116	2	8	610	4171

SELTEX R4-X

SAE J 517 R4

Ekstra Esnek

Hidrolik yağlara ve yakıtlara dayanıklı özel sentetik kauçuk, iş ve tarım makinelerinde hidrolik sistemlerin dönüş devrelerinde. Yüksek esneklik.



İÇ	DÇ	ÇB	PB	KYÇ/r	Ağr
inch	mm	bar	bar	mm	gr/m
3/4"	29	21	84	50	522
1"	35	17	68	65	638
1 1/4"	42	14	56	85	825
1 1/2"	49	10	40	95	1075
2"	62	7	28	135	1544
2 1/2"	75.5	4	16	180	2018
3"	88	4	16	225	2505
3 1/2"	103	3	12	270	3162
4"	115	2	8	390	3635