

SKY-10

HAFİF HİZMET HAVA

TS EN - ISO 2398 TİP1 SINIF A

Tabi ve sentetik kauçuktan mamul, hava ile çalışan aletlerde ve basınçlı hava tahliyesinde.



İÇ	DÇ	ÇB	PB	Ağr
inch	mm	bar	bar	gr/m
1/2"	22	10	40	400
5/8"	25	10	40	444
3/4"	29	10	40	564
1"	36	10	40	661
1 1/8"	39	10	40	866
1 1/4"	44	10	40	1051
1 1/2"	51	10	40	1341
1 3/4"	57	10	40	1426
2"	63	10	40	1619
2 1/2"	78	10	40	2368
2 3/4"	84	10	40	2519
3"	92	10	40	3074
4"	117	10	40	3828

SKY-20

NORMAL HİZMET HAVA

TS EN - ISO 2398 TİP2 SINIF A

Tabi ve sentetik kauçuktan mamul, basınçlı hava naklinde, özellikle maden ocaklarında.



İÇ	DÇ	ÇB	PB	Ağr
inch	mm	bar	bar	gr/m
1/2"	22	16	64	332
5/8"	25	16	64	374
3/4"	29	16	64	504
1"	36	16	64	670
1 1/4"	44	16	64	955
1 1/2"	51	16	64	1177
1 3/4"	60	16	64	1630
2"	65	16	64	1655
2 1/2"	80	16	64	2450
2 3/4"	85	16	64	2600
3"	92	16	64	2650
4"	118	16	64	3810

SKY-25

AĞIR HİZMET HAVA

TS EN - ISO 2398 TİP3 SINIF A

Tabi ve sentetik kauçuktan mamul, basınçlı hava naklinde, maden ocaklarında, inşaatlarda.



İÇ	DÇ	ÇB	PB	Ağr
inch	mm	bar	bar	gr/m
1/2"	23	25	100	380
5/8"	26	25	100	450
3/4"	30	25	100	570
1"	37	25	100	720
1 1/4"	44	25	100	950
1 1/2"	51	25	100	1210
1 3/4"	60	25	100	1660
2"	66	25	100	1825
2 1/2"	80	25	100	2505
2 3/4"	86	25	100	2665
3"	92	25	100	2785
4"	118	25	100	3530

MOON-40

ÇELİK TEL ÖRGÜLÜ HAVA

Yağa dayanıklı, sentetik nitril kauçuktan mamul, çelik tel takviyeli olup maden ocaklarında ve yüksek basınçlı hava tahliyesinde



İÇ	DÇ	ÇB	PB	Ağr
inch	mm	bar	bar	gr/m
1/2"	23	40	160	511
3/4"	29.5	40	160	630
1"	36	40	160	880
1 1/4"	43	40	160	1110
1 1/2"	50	40	160	1540
2"	66	40	160	2515
2 1/2"	80	40	160	3360
3"	94	40	160	4500
4"	122	40	160	6771