

BUHAR VE SICAK SU HORTUMLARI

BUHAR 1A

BEZLİ BUHAR

TS EN ISO 6134 TİP 1 CLASS A

165 °C doymuş buhara dayanıklı EPM kauçuktan mamul, buhar tahliye işlerinde, genel sanayi kullanımında.



İÇ	DÇ	ÇB	PB	Ağr
inch	mm	bar	bar	gr/m
1/2"	25	6	60	390
5/8"	30	6	60	560
3/4"	33	6	60	630
1"	40	6	60	811
1 1/4"	48	6	60	1130
1 1/2"	54	6	60	1275
1 3/4"	60	6	60	1540
2"	69	6	60	1885
2 1/2"	81	6	60	2226
3"	94	6	60	2758
4"	122	6	60	4020

BUHAR 170

BEZLİ BUHAR

165 °C doymuş buhara dayanıklı EPM kauçuktan mamul, buhar tahliye işlerinde, genel sanayi kullanımında.



İÇ	DÇ	ÇB	PB	Ağr
inch	mm	bar	bar	gr/m
1/2"	24	7	70	322
5/8"	28	7	70	456
3/4"	31	7	70	525
1"	37	7	70	610
1 1/4"	46	7	70	942
1 1/2"	53	7	70	1166
1 3/4"	60	7	70	1400
2"	67.5	7	70	1747
2 1/2"	81	7	70	2229
3"	98	7	70	3312
4"	124	7	70	4443

GEYSER-2A

ÇELİK TEL ÖRGÜLÜ BUHAR

TS EN ISO 6134 TİP 2 CLASS A

210 C'ye kadar doymuş buhara dayanıklı EPM kauçuktan mamul, buhar tahliye işlerinde, rafinerilerde, haddanelerde, kimya sanayiinde, tersanelerde.



İÇ	DÇ	ÇB	PB	Ağr
inch	mm	bar	bar	gr/m
1/2"	25	18	180	530
5/8"	30	18	180	750
3/4"	33	18	180	780
1"	40	18	180	1025
1 1/4"	48	18	180	1410
1 1/2"	54	18	180	1775
2"	69	18	180	2580
2 1/2"	81	18	180	3160

BUHAR-SW

ÇELİK TEL ÖRGÜLÜ BUHAR

BS 5342 TYPE 2 CLASS A

200 C'ye kadar doymuş buhara dayanıklı EPM kauçuktan mamul, buhar tahliye işlerinde, rafinerilerde, haddanelerde, kimya sanayiinde, tersanelerde.



İÇ	DÇ	ÇB	PB	Ağr
inch	mm	bar	bar	gr/m
1/2"	24	17	170	485
5/8"	27	17	170	555
3/4"	32	17	170	720
1"	38.5	17	170	955
1 1/4"	46	17	170	1265
1 1/2"	52	17	170	1580
2"	67	17	170	2365
2 1/2"	79.5	17	170	2970