

SIVA 40

BETON ENJEKSİYON

Aşınmaya dayanıklı, iletken tabii kauçuktan mamul, siva, şap, harç, alçı ve hazır betonun makine ile transfer ve püskürtme işlemlerinde



İÇ	DÇ	ÇB	PB	Ağr
inch	mm	bar	bar	gr/m
3/4"	31	40	120	90
1"	38	40	120	110
1 1/4"	46	40	120	160
1 3/8"	49	40	120	175
1 1/2"	54	40	120	190
2"	68	40	120	280
2 3/8"	80	40	120	340
2 1/2"	83.5	40	120	375
2 5/8"	85	40	120	390
3"	96	40	120	440
4"	122	40	120	580
5"	156	40	120	750

SILOBAS

SILOBAS

Aşınmaya dayanıklı iletken tabii kauçuktan mamul, kamyon ve silolardan her türlü kuru çimento, aşındırıcı toz, kireç gibi maddelerin nakil işlerinde.



İÇ	DÇ	ÇB	PB	Ağr
inch	mm	bar	bar	gr/m
2"	60.4	5	15	960
2 1/2"	73	5	15	1175
3"	86	5	15	1392
3 1/2"	100	5	15	1770
4"	112	5	15	2025
4"	115	5	15	2550
4"	117	5	15	3177
5"	137	5	15	3276
6"	164	5	15	3414
8"	215	5	15	4660

BETON UÇ 85

RAKORLU BETON UÇ

Aşınmaya dayanıklı iletken tabii ve CBR kauçuktan mamul, her türlü hazır beton pompalama ve dökme işlerinde.



İÇ	BOY
inch	mt
4"	1.5
4"	2
4"	3
4"	4
4"	5
4"	6
5"	1.5
5"	2
5"	3
5"	4
5"	5
5"	6